

ABT Paging Phone Station

ICO DESKTOP 01

- ✓ 20 SIP lines, 3-way conference, hotspot
- ✓ HD audio on speakerphone and handset
- ✓ Movable type Directional External Gooseneck Microphone
- ✓ 4.3" main color display, 2 x 3.5" side color displays for DSS keys
- ✓ Built-in Bluetooth
- ✓ Wi-Fi connectivity (Via Wi-Fi dongle)
- ✓ Up to 106 DSS keys (42 tri-colored physical keys)
- ✓ Video Codec H.264 support for receiving video calls
- ✓ Dual Gigabit ports, integrated PoE
- ✓ Stand with 2 adjustable angles of 40 and 50 degrees
- ✓ Compatible with major platforms: Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya etc.



MODEL	Screen	Network	PoE	Power adapter
ABT-ICDG-1	4.3" Color-screen	10/100/1000 Mbps	W	—
ABT-ICDG-1B	4.3" Color-screen Increased IK08	10/100/1000 Mbps	W	—

ABT-ICDG-1 is a phone paging station with visualization for business clients. It is equipped with a gooseneck microphone for easy voice messaging and high-quality hands-free connections. Programmable

buttons allow to perform various actions with one click, from voice call, broadcasting to door opening and many more. Communication is based on the SIP protocol and can serve as a monitoring center or

host for an office manager. ABT-ICDG-1 also gives the possibility of quick response in crisis situations.

PHYSICAL SPECIFICATION	
Main LCD ×1	4.3" (480 × 272) color-screen LCD
DSS Key-mapping LCD ×2	3.5" (320 × 480) color-screen LCD
Keypad	77 keys, including: <ul style="list-style-type: none"> » 4 Soft-keys » 6 Function keys (Hold, Call forward, Phonebook, MWI, Headset, Redial) » 4 Navigation keys » 1 OK key » 1 Return key » 12 Standard Phone Digits keys » 3 Volume Control keys, Up/Down/Mute(Microphone) » 1 Hands-free key » 42 DSS Keys with tri-color LED » 3 Page-Switch (PS) key
HD Handset (RJ9)	×1
Standard RJ9 Handset Wire	×1
1.5M CAT5 Ethernet Cable	×1
Gooseneck Microphone	×1 <ul style="list-style-type: none"> » Directional microphone » Frequency response: 20 Hz ~ 20 kHz » SNR: ≥ 60 dB. 1 kHz at 1 Pa
Back Rack	×1
Gooseneck MIC Port ×1	Gooseneck Microphone ×1
RJ9 Port ×2	Handset ×1, Headset ×1
RJ45 Port ×2	Network ×1, PC ×1 (Bridged to Network)
USB2.0 Port ×1	Standard A, Connect with Wi-Fi USB dongle or Flash Driver
DC Power Input	5V / 2A
Power Consumption (PoE)	2.6–9W
Power Consumption (Adapter)	2.4–8W
Working Temperature	0–45°C
Working Humidity	10–95%
Installation	Desktop Stand
Color	Dark gray
Device Dimensions	Desktop Stand (Angles 1): 309 × 214 × 187 mm Desktop Stand (Angles 2): 309 × 226 × 167 mm
Gift Box Dimensions	323 × 301 × 71 mm
Outer CTN Dimensions	624 × 383 × 348 mm (10 PCS)