

ABT-DM3

ZONE MICROPHONE

- ✓ *4.3-inch touchscreen LCD display*
- ✓ *Support for live broadcasts and playback from the microphone's built-in memory*
- ✓ *Function for selecting a group or individual zone from the screen or using the knob*
- ✓ *Possibility to create up to 64 zone groups*
- ✓ *Maximum CAT5e cable length up to 100 meters*



The ABT-DM3 zone microphone is designed to work with the ABT-MX6 and ABT-MX12 audio matrices as a device for playing live messages from the microphone and from the device memory. It supports all matrix outputs and allows you to create up to 64 zone groups. It is equipped with a 4.3-inch touchscreen LCD

display. The microphone has a knob for selecting zones and messages and a PTT button that activates the transmission of the signal from the microphone. The button has an LED indicating operation. Audio files can be uploaded using the USB port.



	ABT-DM3
Electrical Parameters	
Power Supply	15 VDC @ 800 mA
Phantom Power	24 VDC @ 100 mA (software switchable)
Interfaces	
RD IN input (to matrix)	RJ45, CAT-5e cable, 100 m
RD LINK input (for linking)	RJ45, CAT-5e cable, 100 m
USB	supports MP3 sound files (up to 4 s)
Microphone input	3-pin XLR connector (female)
Mechanical Parameters	
Dimensions	166 × 162 × 53 mm (W × D × H)
Weight	1,473 kg

